



STORM VALVE

STRAIGHT PATTERN(VERTICAL)

TYPE WITH CLOSING DEVICE



TECHNICAL FEATURES

Body	Ductile iron / Cast steel / Stainless steel / Bronze
Stem/seat	Bronze or Stainless steel
Design	DIN 87101 Form B - with closing device and handwheel
Face to Face	EN 558 Series 48 (DIN 3202 F6)
Flange Dimension	DIN Flanges acc. to EN 1092/A (DIN 2501)
Pressure Rating	PN 4
Temperature Range	-10 °C...+60 °C
Options	With indicator
Flange Options	Special fl ange drilling acc. to ANSI or JIS

- Storm valves with flat faced DIN flanges and NBR vulcanized disc and closing device with handwheel, prevent sea water entering this system during heavy sea.
- Application: Mainly installed in sanitary piping systems which have a ship's side exit.

DIMENSIONS

DN (mm)	ØD (mm)	L (mm)	H (mm)	H1 (mm)	ØR (MM)	Weight (kg)
50	165	200	140	310	140	16
65	185	240	150	350	140	22
80	200	260	185	390	140	27
100	220	300	200	435	140	35
125	250	350	220	495	160	50
150	285	400	245	530	160	67
200	340	500	315	625	160	101
250	395	600	400	750	200	150
300	445	700	400	900	200	240

