

SEAMLESS CARBON STEEL WELDING HALF PIPE NIPPLE BLACK COATING NF EN 10241 BSP

Seamless carbon steel welding half pipe nipple black coating for liquids, water and compressed air. Designing according to NF EN 10241.

Deburring on each threaded parts



Size: DN3/8" to DN3"

Connection: Male BSP-BW

Min Temperature : -20°C **Max Temperature :** +300°C

Specifications: Deburring on each threaded parts

Chamfer on welding part

Designing according to NF EN 10241

Black coating

Materials: Carbon steel S235



SEAMLESS CARBON STEEL WELDING HALF PIPE NIPPLE BLACK COATING NF EN 10241 BSP

SPECIFICATIONS:

- · Deburring on each threaded part
- Male BSP conical ends according to ISO 7-1 R
- Designing according to EN 10241
- Black coating
- Carbon steel S235
- Fittings tested at 50 bars according to EN 10241

USE :

- · Liquids and compressed air
- Min and max Temperature Ts: 20°C to + 300°C


RANGE:

• Welding half-nipple length 100 mm black coating from DN3/8" to DN 3"



SEAMLESS CARBON STEEL WELDING HALF PIPE NIPPLE BLACK COATING NF EN 10241 BSP

WELDING HALF-PIPE SIZE ART. 530AT3N100 Length 100 mm (in mm):



3/8"	1/2"	3/4"	1"	1"1/4
12x17	15x21	20x27	26x34	33x42
100	100	100	100	100
16.7	21	26.5	33.3	42
2.3	2.6	2.6	3.2	3.2
0.08	0.12	0.16	0.21	0.28
	12x17 100 16.7 2.3	12x17 15x21 100 100 16.7 21 2.3 2.6	12x17 15x21 20x27 100 100 100 16.7 21 26.5 2.3 2.6 2.6	12x17 15x21 20x27 26x34 100 100 100 100 16.7 21 26.5 33.3 2.3 2.6 2.6 3.2

NPS	1"1/2	2"	2"1/2	3"
DN (mm)	40x49	50x60	66x76	80x90
L	100	100	100	100
Ø E mini	47.9	59.7	75.3	88
Т	3.2	3.6	3.6	4
Weight (Kg)	0.34	0.46	0.79	0.98

STANDARDS:

- Manufacturer certified ISO 9001:2015
- DIRECTIVE 2014/68/EU: Products excluded from directive (article 4, § 3)
- Designing according to NF EN 10241
- Male BSP conical ends according to ISO 7-1 R
- Fittings tested at 50 bars according to EN 10241