

## Gate valve with Indicator Non Rising Stem DIN Lenght

### Technical features

Standard	DIN EN 1984 (DIN 3352 T2) -with indicator
Face to face	EN 558 Series 14 (DIN 3202 F4)
Flange dimension	DIN Flanges acc. to EN 1092-1/B (DIN 2501)
Flange connection	PN10/16

- Cast Steel gate valves with stainless steel seats and indicator, raised faced flanges acc. to DIN, bolted bonnet and adjustable gland and short face to face. Inside screwed stem, non-rising stem and handwheel.

- Application: Cold and hot water, fresh water, lubricating oil.

### Pressure & temperature ranges

Bore	Pressure rating	Working pressure [bar]		
		120 °C	Casing	Closure
DN 40- DN 200	PN16	16	24	17.6
DN 250 - DN 300	PN10	10	15	11
DN 350 - DN 500	PN6	6	9	6.6
DN 600 - DN 700	PN4	4	6	4.4



### Material specifications

Part No.	Component	Material		
1	Body	GP240GH	1.0619	GSC25
2	Bonnet	GP240GH	1.0619	GSC25
3	Wedge	GP240GH	1.0619	GSC25
4	Seats	X5CrNi18-10	1.4301	AISI304
5	Stem	X20Cr13	1.4021	AISI420
6	Bolts, nuts	Steel	Steel	Steel
7	Bonnet gasket	Asbestos-free	Asbestos-free	Asbestos-free
8	Gland packing	PTFE	PTFE	PTFE
9	Handwheel	EN-GJL250	EN-JL 1040	GG25
10	Indicator	CuSn5Zn5Pb5-C	CC491K	RG5

### Dimensions

DN [mm]	Flange Connection	OD [mm]	L [mm]	H [mm]	OR [mm]	Weight [kg]
40	PN16	150	140	270	140	12
50	PN16	165	150	270	140	14
65	PN16	185	170	295	160	19
80	PN16	200	180	325	160	22
100	PN16	220	190	360	200	30
125	PN16	250	200	450	200	42
150	PN16	285	210	500	200	53
175	PN16	315	220	560	200	67
200	PN16	340	230	620	250	86
200	PN10	340	230	620	250	86
250	PN10	395	250	730	315	140
300	PN10	445	270	860	315	180
350	PN10	505	290	960	400	245
400	PN10	565	310	1015	400	325
450	PN10	615	330	1125	400	385
500	PN10	670	350	1255	500	535
600	PN10	780	390	1460	500	660
700	PN10	895	430	1715	630	852

