

Bulkhead flange 1 side threaded Stainless steel



Material:1.4571-316Ti

DIN 28117/A

DN	D	b	k	d6	hole	RG	t	PN	kg
15	95	25	65	15	4	M12	18	40	1,326
20	105	25	75	20	4	M12	18	40	1,609
25	115	25	85	25	4	M12	18	40	1,920
32	140	30	100	32	4	M16	23	40	3,364
40	150	30	110	40	4	M16	23	40	3,776
50	165	30	125	50	4	M16	23	40	4,472
65	185	30	145	65	4	M16	23	16	5,710
65	185	30	145	65	8	M16	23	40	5,470
80	200	30	160	80	8	M16	23	40	6,040
100	220	30	180	100	8	M16	23	16	8,000
100	235	36	190	100	8	M20	28	40	9,920
125	250	30	210	125	8	M16	23	16	8,500
125	270	42	220	125	8	M24	33	40	14,370
150	285	30	240	150	8	M20	28	16	13,000
150	285	36	240	150	8	M20	28	16	12,833
150	300	42	250	150	8	M24	33	40	17,020
200	340	36	295	200	8	M20	28	10	16,500
200	340	36	295	200	12	M20	28	16	16,276
250	395	36	350	250	12	M20	28	10	20,600
250	405	42	355	250	12	M24	33	16	20,000
300	445	36	400	300	12	M20	28	10	24,000
300	460	42	410	300	12	M24	33	16	35,700
350	505	36	460	350	16	M20	28	10	23,300
400	565	42	515	400	16	M24	32	10	39,560
400	580	45	525	400	16	M27	36	16	47,000
500	670	42	620	500	20	M24	33	10	50,000

